

A photograph of a modern office hallway. The hallway is lined with glass-walled rooms on the left side. Each room has a silver electronic door lock mounted on the glass. The hallway is carpeted and has recessed ceiling lights. The perspective is from the end of the hallway, looking down its length.

ELECTRONIC LOCK

Euro Electronic locks can be retrofitted into any standard European door. Users can use Card, Pin, or Mobile Phone to open the door. IP67 Electronic Lock can even operate under raining. All electronic locks are capable for application such as airport, hospital, banking, hotel, commercial building, school campus, residential, and so on.



L701

Keypad Electronic Lock

SPECIFICATIONS:

- Axis Distance : 70 mm, 72 mm, 85 mm, 92 mm
- Door Thickness: 40 mm ~ 120 mm
- Transponder: Mifare Classic
 - Desfire
 - 2.4G RF
 - Pin Code
- Reading Distance up to 30 mm
- Battery Life: 60,000 Operations or 5 Years Standby
- Battery: CR2 x 1 pcs
- Operation Temperature: -20°C ~ 60°C
- Smart Sleep Mode
- Acoustic Low Power Warning
- Firmware Upgradeable
- CE Certificate
- **Option:** Mechanical Cylinder Hole on Escutcheon for Override
- **Option:** Thin Escutcheon



APPLICATION:

Standalone	L701
------------	------

